

**SHAW 4100 REXCOURT/VINYL FLOORING  
ADH**

Version	Revision Date:	MSDS Number:	Date of last issue: 05/28/2015
4.0	06/10/2015	F000001329	Date of first issue: 05/21/2015

---

**SECTION 1. IDENTIFICATION**

Product name : SHAW 4100 REXCOURT/VINYL FLOORING ADH

Product code : F000001329

**Manufacturer or supplier's details**

Company name of supplier : Shaw Industries

Address : 616 East Walnut Avenue  
Dalton GA 30721

Telephone : (706) 275-3688

Telefax :

Emergency telephone number : (CHEMTREC): (800) 424-9300 (CHEMTREC International):  
(703) 527-3887 Industrial Health/Spill Emergency: (706) 277-  
1300 Danny Welch (ehs@trcc.com)

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Not a hazardous substance or mixture.

**GHS Label element**

Not a hazardous substance or mixture.

**Other hazards**

None known

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

No hazardous ingredients

---

**SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air in case of accidental inhalation of vapours.  
Oxygen or artificial respiration if needed.  
Call a physician or poison control centre immediately.

In case of skin contact : Wash off immediately with soap and plenty of water while  
removing all contaminated clothes and shoes.  
If skin irritation persists, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse imme-

## SHAW 4100 REXCOURT/VINYL FLOORING ADH

Version 4.0	Revision Date: 06/10/2015	MSDS Number: F000001329	Date of last issue: 05/28/2015 Date of first issue: 05/21/2015
----------------	------------------------------	----------------------------	---

---

diately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
Seek medical advice.

If swallowed : Do not induce vomiting without medical advice.  
If conscious, drink plenty of water.  
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : None known.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam  
Carbon dioxide (CO<sub>2</sub>)  
ABC powder  
Water mist

Specific hazards during fire-fighting : Burning produces irritant fumes.  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Material can create slippery conditions.  
Use non-slip safety shoes in areas where spills or leaks can occur.

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Do not let product enter drains.

---

## SHAW 4100 REXCOURT/VINYL FLOORING ADH

Version 4.0	Revision Date: 06/10/2015	MSDS Number: F000001329	Date of last issue: 05/28/2015 Date of first issue: 05/21/2015
----------------	------------------------------	----------------------------	---

---

Do not allow contact with soil, surface or ground water.  
Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Dam up.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up and shovel.  
Pick up and transfer to properly labelled containers.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : The product is not flammable. No special protective measures against fire required.

Advice on safe handling : Wear personal protective equipment.  
Handle with care.  
Take care to avoid waste and spillage when weighing, loading and mixing the product.

Conditions for safe storage : No smoking.  
Keep in properly labelled containers.  
Observe label precautions.  
Keep containers tightly closed in a dry, cool and well-ventilated place.

Materials to avoid : Do not freeze.  
Keep away from food and drink.  
Keep away from tobacco products.

Recommended storage temperature : 4 - 43 °C

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : Handle only in a place equipped with local exhaust (or other appropriate exhaust).  
Maintain air concentrations below occupational exposure standards.

#### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**SHAW 4100 REXCOURT/VINYL FLOORING  
ADH**

Version	Revision Date:	MSDS Number:	Date of last issue: 05/28/2015
4.0	06/10/2015	F000001329	Date of first issue: 05/21/2015

---

Use NIOSH approved respiratory protection.

Hand protection  
Material

: Impervious gloves

Eye protection

: Safety glasses with side-shields  
Tightly fitting safety goggles  
Face-shield

Skin and body protection

: Chemical resistant apron  
Footwear protecting against chemicals  
Skin should be washed after contact.  
Change working clothes after each workshift.

Protective measures

: Avoid contact with skin.  
When using do not eat, drink or smoke.  
Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing  
The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

: Do not smoke.  
Keep away from food and drink.  
Avoid contact with skin, eyes and clothing.  
Change working clothes after each workshift.  
Remove and wash contaminated clothing and gloves, including the inside, before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: paste
Colour	: white
Odour	: mild, characteristic
pH	: 7.8 - 8.5
Melting point/range	: No data available
Boiling point/boiling range	: 212 °F
Flash point	: > 212 °F
Vapour pressure	: similar to water
Density	: 1,100 - 1,160 kg/m <sup>3</sup>
Solubility(ies)	

**SHAW 4100 REXCOURT/VINYL FLOORING  
ADH**

Version	Revision Date:	MSDS Number:	Date of last issue: 05/28/2015
4.0	06/10/2015	F000001329	Date of first issue: 05/21/2015

---

Water solubility	:	insoluble
Solubility in other solvents	:	Not applicable
Partition coefficient: n-octanol/water	:	No data available
Explosive properties	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Stable
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Protect from frost.
Incompatible materials	:	Oxidizing agents Strong acids and strong bases
Hazardous decomposition products	:	Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), dense black smoke.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	:	Remarks: This information is not available.
Acute inhalation toxicity	:	Remarks: This information is not available.
Acute dermal toxicity	:	Remarks: This information is not available.

**Skin corrosion/irritation****Product:**

Remarks: This information is not available.

**Serious eye damage/eye irritation****Product:**

Remarks: This information is not available.

**Respiratory or skin sensitisation****Product:**

## SHAW 4100 REXCOURT/VINYL FLOORING ADH

Version 4.0	Revision Date: 06/10/2015	MSDS Number: F000001329	Date of last issue: 05/28/2015 Date of first issue: 05/21/2015
----------------	------------------------------	----------------------------	---

---

Remarks: This information is not available.

### Carcinogenicity

#### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates :  
Remarks: No data available

Toxicity to algae :  
Remarks: No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.  
Can be landfilled or incinerated, when in compliance with local regulations.

**SHAW 4100 REXCOURT/VINYL FLOORING  
ADH**

Version 4.0	Revision Date: 06/10/2015	MSDS Number: F000001329	Date of last issue: 05/28/2015 Date of first issue: 05/21/2015
----------------	------------------------------	----------------------------	---

---

Contaminated packaging : Clean container with water.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulation****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**49 CFR**

Not regulated as a dangerous good

---

**SECTION 15. REGULATORY INFORMATION**

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**TSCA** All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).


## SHAW 4100 REXCOURT/VINYL FLOORING ADH

Version 4.0      Revision Date: 06/10/2015      MSDS Number: F000001329      Date of last issue: 05/28/2015  
Date of first issue: 05/21/2015

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



##### HMIS III:

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 06/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN