

## Safety Data Sheet

acc. to OSHA HCS

Printing date 01/03/2019

Reviewed on 01/03/2019

### 1 Identification

- **Product identifier**
- **Trade name: AAT-675**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Advanced Adhesive Technologies, LLC.  
424 S Spencer St  
Dalton, GA 30721  
Tel: 800-228-4583  
Fax: 706-278-6207
- **Emergency telephone number:**  
CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2      H351 Suspected of causing cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word Warning**

- **Hazard-determining components of labeling:**

ethyl acrylate

1,2-benzisothiazol-3(2H)-one

- **Hazard statements**

May cause an allergic skin reaction.

Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

**Safety Data Sheet**  
acc. to OSHA HCS



Printing date 01/03/2019

Reviewed on 01/03/2019

**Trade name: AAT-675**

(Contd. of page 1)

Wash contaminated clothing before reuse.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 0  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0
FIRE	0
REACTIVITY	0

Health = 0  
Fire = 0  
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

140-88-5	ethyl acrylate	1.133%
----------	----------------	--------

**4 First-aid measures**

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 01/03/2019

Reviewed on 01/03/2019

Trade name: AAT-675

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
  - Dilute with plenty of water.
  - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Dispose contaminated material as waste according to item 13.
  - Ensure adequate ventilation.
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

140-88-5	ethyl acrylate	8.3 ppm
57-13-6	urea	30 mg/m <sup>3</sup>

### · PAC-2:

140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m <sup>3</sup>

### · PAC-3:

140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
  - Ensure good ventilation/exhaustion at the workplace.
  - Open and handle receptacle with care.
  - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
  - Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
  - Requirements to be met by storerooms and receptacles:** No special requirements.
  - Information about storage in one common storage facility:** Not required.
  - Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 01/03/2019

Reviewed on 01/03/2019

**Trade name: AAT-675**

(Contd. of page 3)

· **Control parameters**

· <b>Components with limit values that require monitoring at the workplace:</b>	
<b>140-88-5 ethyl acrylate</b>	
PEL	Long-term value: 100 mg/m <sup>3</sup> , 25 ppm Skin
REL	See Pocket Guide App. A
TLV	Short-term value: 61 mg/m <sup>3</sup> , 15 ppm Long-term value: 20 mg/m <sup>3</sup> , 5 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling.

**9 Physical and chemical properties**

· <b>Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
Form:	Fluid
Color:	According to product specification
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS



Printing date 01/03/2019

Reviewed on 01/03/2019

Trade name: AAT-675

(Contd. of page 4)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	13.6 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 6)

Printing date 01/03/2019

Reviewed on 01/03/2019

Trade name: AAT-675

(Contd. of page 5)

### 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Oral	LD50	70,609 mg/kg (rat)
Dermal	LD50	161,871 mg/kg (rabbit)
Inhalative	LC50/4 h	192,410 mg/l (rat)

#### 140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

140-88-5 ethyl acrylate	2B
-------------------------	----

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:

- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS



Printing date 01/03/2019

Reviewed on 01/03/2019

**Trade name: AAT-675**

· **Other adverse effects** No further relevant information available. (Contd. of page 6)

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>UN proper shipping name</b>	
· <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>Transport hazard class(es)</b>	
· <b>DOT, ADN, IMDG, IATA</b>	
· <b>Class</b>	not regulated
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	not regulated
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	not regulated

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **TSCA (Toxic Substances Control Act):**

140-88-5	ethyl acrylate
9003-04-7	2-propenoic acid, homopolymer, sodium salt
57-13-6	urea
2634-33-5	1,2-benzisothiazol-3(2H)-one
7732-18-5	water, distilled, conductivity or of similar purity

· **Proposition 65**

· **Chemicals known to cause cancer:**

140-88-5	ethyl acrylate
----------	----------------

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 01/03/2019

Reviewed on 01/03/2019

Trade name: AAT-675

(Contd. of page 7)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

57-13-6 | urea

II

· **TLV (Threshold Limit Value established by ACGIH)**

140-88-5 | ethyl acrylate

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5 | ethyl acrylate

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

ethyl acrylate

1,2-benzisothiazol-3(2H)-one

· **Hazard statements**

May cause an allergic skin reaction.

Suspected of causing cancer.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

US



**Safety Data Sheet**  
acc. to OSHA HCS



Printing date 01/03/2019

Reviewed on 01/03/2019

**Trade name: AAT-675**

(Contd. of page 8)

- **Department issuing SDS:** Technical Department
- **Contact:** Technical Director
- **Abbreviations and acronyms:**
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMSI: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - Skin Sens. 1: Skin sensitisation – Category 1
  - Carc. 2: Carcinogenicity – Category 2

US