

# Innovative Coatings LLC

## I-Coat™

### Part Number IC-1001B (Revision 4)

#### Construction

<b>Top Liner</b>	<b>60# Poly coated liner-Printed- C2S(SL4/SL1)</b>
<b>Adhesive</b>	Removable IC Adhesive - 3.0 mils
<b>Carrier</b>	3 Mil gauge PET film- Printed
<b>Adhesive</b>	Permanent Adhesive - 3 mils
<b>Bottom Liner</b>	1.5 Mil PET Film-C2S
<b>Die Cut</b>	Yes

#### Typical Performance Properties

Removable Adhesive Side:	Loop Tack: 400-550 grams
Permanent Side:	180 Degree Peel: 3500-4000 grams
High Operating Range:	150 F
Low Operating Range:	-10 F

#### Size

Die Cut/500 pieces/Roll  
Die Cut Dimensions per Shaw

#### Application: Shaw Lok Worx

**Testing:** Always test the suitability of the product for your application before use.

**Health and Safety Information:** This product is an “article” and does not require a safety data sheet.

**Note:** The user is responsible for determining whether this product, surface preparation and method of assembly are suitable for their particular purpose. Failure to determine the suitability of all factors involved in the application may result in bond failures.

### Innovative Coatings LLC

N117 W18654 Fulton Drive, Germantown, WI 53022

1-877-534-5006/www.i-coatings.com

*‘Innovative Technology for Demanding Removable Applications’*

**Revision-4 (May 9, 2016)**